

- Sleek black aluminum interior
- Black powder coated steel exterior
- Forced air refrigeration system which maintains 33°– 41°F (0.5°– 5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product

#### ORGANIZATION

- Two adjustable heavy-duty PVC coated black wire shelves allow for adjustable organization options
  - Shelf dimensions: 19<sup>5</sup>/<sub>8</sub>"W x 17"L

# SPECIFICATIONS

Dimensions (w x h x d)	23 <sup>7</sup> /s" x 31 <sup>7</sup> /s" x 23 <sup>5</sup> /32"
Capacity (cu. ft.)	5.0
Temperature Range	33°- 41°F (0.5°- 5°C)
Weight (Ibs.)	145
Voltage	115/60/1 115/60/1 NEMA-5-15R
Amps	0.8
Annual Energy Consumption (kWh)	275
Power Cord Length (ft.)	10
Energy Star Rated	Yes

#### WARRANTY

•	•			•	•	• •	•	•	•	•	•		۰	•	•		•	•	• •				•	•	• •		•	• •		•	• •	•	•	•		•	• •		•	• •			•	•	• •	۰	•	• •	0	
	~	, ,		. ~		f,	.1			~		. re	ŀc	ç	,	1-	h	_	۲		5				٦r	~	~	~1	_	А	~		-+	~	~			~ ~	٦r	to		p	1-			٥r				
	4		Ye	=c	11		JI		_	ŀ	C	11	ιs	C	x	IC	IJ	0	1	•	9	2	Ye	=c	11	З	e	сП	e	u	5	y:	sι	e			- ŀ	Jo	11	15	0	x	IC	11		1				







- Sleek black aluminum interior
- Black powder coated steel exterior
- Five pull-out PVC coated wire wine racks for storage of 7 bottles each and one floor wine cradle for storage of 5 bottles, 40 bottles total.
- Forced air refrigeration system which maintains 40°- 65°F (4.4°- 18.3°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product

# ORGANIZATION

- Five pull-out PVC coated wire wine racks for storage of 7 bottles each
  - Shelf dimensions:  $17\,\%$  W x  $16\,\%$  L
- One floor wine cradle for storage of 5 bottles

## SPECIFICATIONS

Dimensions (w x h x d)	23 %" x 31%" x 23 <sup>5</sup> /32"
	• • • • • • • • • • • • • • • • • • • •
Capacity (bottles)	40
Temperature Range	40°- 65°F (4.4°- 18.3°C)
Weight (Ibs.)	225
Voltage	115/60/1 115/60/1 NEMA-5-15R
	$\bigcirc$
Amps	0.8
Amps Annual Energy Consumption (kWh)	0.8
	0.8
Annual Energy Consumption (kWh)	0.8

# WARRANTY

2 year full – parts & labor • 5 year sealed system – parts & labor







- Sleek black aluminum interior
- Black powder coated steel exterior
- One pull-out PVC coated wire wine rack and one floor wine cradle for storage of 12 total bottles
- Forced air refrigeration system which maintains 33°– 41°F (0.5°– 5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product

## ORGANIZATION

- Two adjustable heavy-duty PVC coated black wire shelves allow for adjustable organization options
  - Shelf dimensions: 19%"W x 17"L
- One pull-out PVC coated wire wine rack for storage of 7 bottles
  - Shelf dimensions: 17% W x 16% L
- One floor wine cradle for storage of 5 bottles

# SPECIFICATIONS

••••••
23 <sup>7</sup> / <sub>8</sub> " x 31 <sup>7</sup> / <sub>8</sub> " x 23 <sup>5</sup> / <sub>32</sub> "
5.0
33°- 41°F (0.5°- 5°C)
145
115/60/1 115/60/1 NEMA-5-15R
0.8
275
10
Yes





# WARRANTY

2 year full – parts & labor • 5 year sealed system – parts & labor



- Sleek black aluminum interior stainless steel drawer bin inserts
- Black powder coated steel exterior
- Forced air refrigeration system which maintains 33°– 41°F (0.5°– 5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product

#### SPECIFICATIONS

Dimensions (w x h x d)	237⁄8" × 317⁄8" × 23 <sup>5</sup> ⁄32"
Capacity (cu. ft.)	5.0
Temperature Range	33°- 41°F (0.5°- 5°C)
Weight (lbs.)	190
Voltage	115/60/1 (I) 115/60/1 NEMA-5-15R
Amps	0.8
Amps	0.8
Amps Annual Energy Consumption (kWh)	0.8 273

#### WARRANTY

	• •		• •		0	• •	•	۰	• •	• •	•	• •	•	• •	۰	• •		0	• •		• •	• •		• •		• •		•	• •	•		• •		• •	• •		•	• •	• •		• •	•	0	•
2	2 )	/e	a	r i	fu	ıII	_	٠Ķ	C	art	ts	&	la	ak	0	r	٠	5	У	ea	ar	S	e	al	e	d	S	/S	te	er	n	_	р	a	rt	S	8	۱ <u>،</u>	а	b	or			

