

- · Sleek black aluminum interior
- · Black powder coated steel exterior
- Forced air refrigeration system which maintains  $33^{\circ}-41^{\circ}F$  (0.5°-5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product
- · UL-rated for outdoor use
- · Lock standard on stainless steel models
- · Field-reversible hinge allows for flexibility in the field

#### **ORGANIZATION**

- Two adjustable heavy-duty PVC coated black wire shelves allow for adjustable organization options
  - Shelf dimensions: 19 5/8 "W x 17" L



Dimensions (w x h x d)	23½" × 31½" × 23½2"
Capacity (cu. ft.)	5.0
Temperature Range	33°- 41°F (0.5°- 5°C)
Weight (lbs.)	145
Voltage	115/60/1 115/60/1 NEMA-5-15R
Amps	0.8
Annual Energy Consumption (kWh)	275
Power Cord Length (ft.)	10
Energy Star Rated	Yes

# **WARRANTY**

2 year full – parts & labor • 5 year sealed system – parts & labor







- · Sleek black aluminum interior
- Black powder coated steel exterior
- Five pull-out PVC coated wire wine racks for storage of 7 bottles each and one floor wine cradle for storage of 5 bottles, 40 bottles total.
- Forced air refrigeration system which maintains 40°– 65°F (4.4°– 18.3°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- · White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product
- · Field-reversible hinge allows for flexibility in the field
- · UL-rated for outdoor use
- · Lock standard on stainless steel models

## **ORGANIZATION**

- Five pull-out PVC coated wire wine racks for storage of 7 bottles each
  - Shelf dimensions: 17 % "W x 16 %" L
- One floor wine cradle for storage of 5 bottles

## **SPECIFICATIONS**

Dimensions (w x h x d)       237/6" x 317/6" x 235/52"         Capacity (bottles)       40         Temperature Range       40°- 65°F (4.4°- 18.3°C)         Weight (lbs.)       225         Voltage       115/60/1         Amps       0.8         Annual Energy Consumption (kWh)       195         Power Cord Length (ft.)       10		
Temperature Range       40°- 65°F (4.4°- 18.3°C)         Weight (lbs.)       225         Voltage       115/60/1         Amps       0.8         Annual Energy Consumption (kWh)       195         Power Cord Length (ft.)       10	Dimensions (w x h x d)	23½" x 31½" x 23½"
Weight (lbs.)  225  Voltage  115/60/1  Amps  0.8  Annual Energy Consumption (kWh)  195  Power Cord Length (ft.)  10	Capacity (bottles)	40
Voltage 115/60/1 115/60/1 NEMA-5-15R  Amps 0.8  Annual Energy Consumption (kWh) 195  Power Cord Length (ft.) 10	Temperature Range	40°- 65°F (4.4°- 18.3°C)
Amps 0.8  Annual Energy Consumption (kWh) 195  Power Cord Length (ft.) 10	Weight (lbs.)	225
Annual Energy Consumption (kWh) 195  Power Cord Length (ft.) 10	Voltage	115/60/1 115/60/1 NEMA-5-15R
Power Cord Length (ft.) 10	Amps	0.8
3. (4)	Annual Energy Consumption (kWh)	195
	Power Cord Length (ft.)	10
Energy Star Rated —	Energy Star Rated	_





## **WARRANTY**

2 year full – parts & labor  $\cdot$  5 year sealed system – parts & labor



- · Sleek black aluminum interior
- Black powder coated steel exterior
- One pull-out PVC coated wire wine rack and one floor wine cradle for storage of 12 total bottles
- Forced air refrigeration system which maintains  $33^{\circ}-41^{\circ}\text{F}$  (0.5°-5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- · White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product
- · Field-reversible hinge allows for flexibility in the field
- · UL-rated for outdoor use
- · Lock standard on stainless steel models

# **ORGANIZATION**

- Two adjustable heavy-duty PVC coated black wire shelves allow for adjustable organization options
  - Shelf dimensions: 19 % "W x 17" L
- One pull-out PVC coated wire wine rack for storage of 7 bottles
  - Shelf dimensions: 17% W x 16% L
- One floor wine cradle for storage of 5 bottles

# **SPECIFICATIONS**

Dimensions (w x h x d)	23½" x 31½" x 23½2"
Capacity	5.0
Temperature Range	33°- 41°F (0.5°- 5°C)
Weight (lbs.)	145
Voltage	115/60/1 115/60/1 NEMA-5-15R
Amps	0.8
Annual Energy Consumption (kWh)	275
Power Cord Length (ft.)	10
Energy Star Rated	Yes





#### **WARRANTY**

2 year full – parts & labor  $\cdot$  5 year sealed system – parts & labor



- Sleek black aluminum interior stainless steel drawer bin inserts
- · 2 adjustable bin dividers per drawer
- Black powder coated steel exterior
- Forced air refrigeration system which maintains 33°– 41°F (0.5°– 5°C)
- Environmentally friendly R600a refrigerant
- Concealed digital temperature controls allows for precise temperature management
- · White LED lighting illuminates your product
- Unit comes standard with 4 adjustable leg levelers
- NSF/ANSI Standard 7 compliant for packaged food product
- · UL-rated for outdoor use



Dimensions (w x h x d)	23 %" × 31%" × 23 <sup>5</sup> / <sub>32</sub> "
C	
Capacity (cu. ft.)	5.0
Temperature Range	33°- 41°F (0.5°- 5°C)
Weight (lbs.)	190
	45504
Voltage	115/60/1 NEMA-5-15R
Amps	0.8
Appropriate Construction (IAA/Ia)	272
Annual Energy Consumption (kWh)	273
Power Cord Length (ft.)	10
Energy Star Rated	Yes

## **WARRANTY**

2 year full – parts & labor  $\cdot$  5 year sealed system – parts & labor

